



## Sisal Wallcovering

Extremely durable. Minimal wall preparation. Sound absorbent.  
Class A Flame Spread. Biodegradable. Ideal for high abuse areas.  
Sisal transforms "institutional" appearances to a warm, natural look.  
A Grown Green Product.

Composition & Construction:	100% Sisal yarn, boucle weave
Pile Height:	¼ "
Weight:	Minimum of 48 oz/sq yard
Type:	Reversible Weave Without Backing
Roll Dimensions:	8' x 100'; 9' x 100'; 13' x 50' Subject to availability
Quality Assurance:	- Class A Flame Spread Rating ASTM-E84 - Passes Corner Burn Test UBC 8-2 & NFPA 265
Acoustical:	NRC Value: .10 avg ASTM C: 423-90a
Static Control:	100% Static Free
Environmental:	LEED Credits available rating sys (USGBC) Rapidly renewable bio-based material Low-emitting materials Grown Green Product
Approved Adhesive:	Fibreworks #257 Sisal Adhesive Instant Tact                      Dries Firm Non-Hazardous                      Low Moisture Latex, Water Soluble              VOC Compliant

Notice: Fibreworks #257 Sisal Adhesive is the only recommended adhesive for Fibreworks Sisal. Fibreworks will not guarantee any installation of sisal when another adhesive is used. If you have any questions, please call Fibreworks.

  
Natural Fiber Wallcovering  
1-800-843-0063 press #3  
2417 Data Drive  
Louisville, KY 40299  
Email: [sean@fibreworks.com](mailto:sean@fibreworks.com)  
[www.fibreworks.com](http://www.fibreworks.com)